Product Data Sheet



K Rend Colour Fill

K Rend Colour Fill is a flexible, ready to use, exterior masonry filler, that is suitable for minor repair work such as small cracks and holes.

Such defects on exterior surfaces are not only unsightly, but left untreated, can leave walls vulnerable to further damage. K Rend Colour Fill offers an ideal solution by providing permanent protection, as well as a tidy finish.

K Rend Colour Fill is specially formulated to ensure

- Good penetration into cracks
- Excellent adhesive properties
- High degree of elasticity
- A textured finish

Preparation

- Surface should be clean, dry, sound and cohesive.
- For fine cracks, it is recommended that the width to around 5-6mm. This is best achieved using an electric multi-cutter with blade attachment.
- This will ensure that when K Rend Colour Fill is applied, the material will have greater integrity to the walls of the crack and therefore prevent the liklihood of reopening.

Application

- Cut nozzle to required size. (Depends on size of crack)
- Remove the tip screw and end cap from the cartridge and fit the nozzle. Apply filler using a standard applicator gun. Ensure that the filler is left proud of the crack.
- Remove excess material using a clean cloth or sponge whilst creating a textured finish on the surface.
- Build filler up in layers, allowing each layer to dry before applying the next. Colour Fill can be applied up to a maximum thickness of 8 mm per coat.
- After addition of final layer, allow the filler to fully cure for about 12-24 hours. (Depending on thickness and weather)
- The cartridge can be made air tight by replacing both the end cap and tip screw.

Overcoating

For optimum blending of repaired area, K Rend Colour Enhance can be applied once the filler is fully cured.

Packaging

- 310 cc cartridges. Each accompanied with a nozzle (4" long, 1/16" ID), an end cap and a tip screw.
- The product has a shelf life of approximately one year if stored fully sealed and protected against frost and away from direct sunlight.

Cleaning

Clean tools and equipment with water immediately after use.

Colours

- K Rend Colour Fill comes in a range of colour.
- Colour of filler can be co-ordinated with any of K Rend's 20 standard silicone scraped textured products.
- It is advised that colour matches may no be exact.

Other Information

Safety: The product is non-hazardous if used according to the manufacturers instructions; a separate material safety data sheet is available upon request.

Technical Advice

- The product must be stored and applied in accordance to the manufacturer's recommendations.
- A technical advisory service is available upon request.

Caution

- The temperature of the substrate and surrounding air should be a minimum of 5^OC before applying.
- Do not apply in conditions of strong sunshine or wind: do not apply onto damp or frozen substrates.
- Drying times may be prolonged by lower temperatures and/or high humidity.

All Specifications are developed and owned by Kilwaughter Chemical Co Ltd for use as internal / external wall coverings. Kilwaughter Chemical Co Ltd use the Specifications in conjunction with its other standard form documents and technical data sheets and in compliance with professional bodies such as RIBA. Kilwaughter Chemical Co Ltd does not use the Specifications for any other purpose and does not consider them suitable for use for any other purpose. Electronic copies of specifications in MS Word format are not to be supplied outside the company. Kilwaughter Chemical Co Ltd does not permit the possession or use of electronic copies of specifications or guides to specifications by non Kilwaughter Chemical Co Ltd organisations or persons other than as stated above. In line with our policy of continuous product development, we reserve the right to change technical data without notice.











